

View Online at <https://aerobasegroup.com/nsn/5340-01-277-4428>

**Mounting Hole Type:**

Plain and threaded

**First Leg Length:**

1.300 inches

**Second Leg Length:**

1.400 inches

**Second Leg Width:**

3.000 inches

**First Leg Hole Diameter:**

0.250 inches

**Second Leg Hole Diameter:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**Center Section Height:**

Between 1.240 inches and 1.250 inches

**Center Section Width:**

3.000 inches

**Center Section Thickness:**

0.350 inches

**First Leg Width:**

3.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.700 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**First Leg Chamfer Angle:**

30.0 degrees

**Special Features:**

Center section has three holes 0.212 in. Min, 0.218 in. Max

**Material:**

Aluminum alloy 2024 or aluminum alloy 6061

**Material Specification:**

Qq-a-225/6, t351 federal specification 1st material response or qq-a-200/8, t6511 federal specification 2nd material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 1, cl 1 military specification single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.