

View Online at <https://aerobasegroup.com/nsn/5340-01-277-7349>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.510 inches

**Second Leg Length:**

1.640 inches

**Second Leg Width:**

0.620 inches

**First Leg Hole Diameter:**

0.098 inches

**Second Leg Hole Diameter:**

0.098 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.750 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.310 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.310 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**First Leg Width:**

0.620 inches

**First Leg Distance Between Hole Centers Along Length:**

0.620 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.310 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.310 inches

**First Leg End Radius:**

0.430 inches

**Second Leg End Radius:**

0.430 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Offset Angle:**

87.0 degrees

**Material:**

Aluminum alloy 7075 and aluminum alloy 7072

**Material Specification:**

Qq-a-250/13 t6 federal specification all material responses

**Surface Treatment:**

Anodize or chromate

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Style Designator:**

Offset angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.