

View Online at <https://aerobasegroup.com/nsn/5340-01-278-2968>

**End Application:**

F-15

**Special Features:**

Palum alloy 2024-t81 per qq-a-250/4; anodized black per ps13201 type 2, class 2; 0.063 in. Thk; 7.095/7.125 in. Lg; 4.980/5.000 in. Wd; item has 3 holes 0.144/0.150 in. Diameter requiring 3 plate nuts p/n ms21075l06, 6 rivets p/n 3m268ad3-5 flush nearside that mates with p/n 68j818040, 6 studs p/n 9m161-1f-388, with c to c distance between studs along lg 2.625 in.(porm 0.005 in.)and 4.616 in.(porm 0.005 in.) along wd; 6 cups p/n 9m161-1cb, 6 springs p/n 9m161-1sb installed per 6m71; requires two p/n 6m62-3-2 cutouts that mate with p/n 68j818040 and one p/n 6m153-1 cutout mating with p/n 68j818040; item also includes 1 alum alloy 2024-0 per qq-a-250/5; 0.050 in. Thk; 2 holes 0.196/0.202 in. Diameter for grd that requires 4 rivets p/n 3m269ad4-5

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530d0