## NSN 5340-01-279-5807

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-279-5807

**Mounting Hole Type:** 

Plain

First Leg Length:

Between 0.750 inches and 0.780 inches

Second Leg Length:

Between 0.750 inches and 0.780 inches

Second Leg Width:

Between 1.230 inches and 1.270 inches

**Second Leg Corner Radius:** 

0.250 inches

First Leg Hole Diameter:

Between 0.1645 inches and 0.1675 inches

Second Leg Hole Diameter:

Between 0.220 inches and 0.230 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.740 inches and 0.760 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.250 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Width:

Between 1.230 inches and 1.270 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.650 inches

First Leg Distance From Edge To Hole Center Along Width:

0.300 inches

First Leg Distance From Edge To Hole Center Along Length:

0.300 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

## NSN 5340-01-279-5807

Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
80.0 degrees
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-250/5, t81 federal specification single material response
Surface Treatment:
Primer
Surface Treatment Specification:
Mil-p-23377 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-p-23377 spec.