

View Online at <https://aerobasegroup.com/nsn/5340-01-279-7077>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.750 inches

**Second Leg Length:**

1.500 inches

**End Application:**

Lau-105

**First Leg Hole Diameter:**

Between 0.204 inches and 0.212 inches

**Second Leg Hole Diameter:**

Between 0.250 inches and 0.258 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.300 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.520 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**Center Section Height:**

2.500 inches

**Center Section Width:**

1.450 inches

**Center Section Thickness:**

0.063 inches

**First Leg End Width:**

1.150 inches

**First Leg Distance Between Hole Centers Along Width:**

0.560 inches

**First Leg Distance Between Hole Centers Along Length:**

0.600 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.350 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Special Features:**

Kcntr section has 1 hole diameter 0.620 in., dist from edge to hole cntr along width 0.700 in., dist along lg 1.000 in. & has 2 holes diameter 0.129 to 0.139 in. On each side, w/cntr to cntr distance along lg and width 0.594 in.

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/4 t3 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Adjacent angles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.