

View Online at <https://aerobasegroup.com/nsn/5340-01-279-7077>

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

1.500 inches

End Application:

Lau-105

First Leg Hole Diameter:

Between 0.204 inches and 0.212 inches

Second Leg Hole Diameter:

Between 0.250 inches and 0.258 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.300 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.520 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

Center Section Height:

2.500 inches

Center Section Width:

1.450 inches

Center Section Thickness:

0.063 inches

First Leg End Width:

1.150 inches

First Leg Distance Between Hole Centers Along Width:

0.560 inches

First Leg Distance Between Hole Centers Along Length:

0.600 inches

First Leg Distance From Edge To Hole Center Along Width:

0.350 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Kcntr section has 1 hole diameter 0.620 in., dist from edge to hole cntr along width 0.700 in., dist along lg 1.000 in. & has 2 holes diameter 0.129 to 0.139 in. On each side, w/cntr to cntr distance along lg and width 0.594 in.

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/4 t3 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.