

View Online at <https://aerobasegroup.com/nsn/5340-01-279-9155>

Mounting Hole Type:

Plain

First Leg Length:

Between 2.380 inches and 3.380 inches

Second Leg Length:

Between 1.360 inches and 1.400 inches

Second Leg Width:

Between 7.734 inches and 7.770 inches

First Leg Hole Diameter:

Between 0.384 inches and 0.396 inches

First Leg Slot Length:

Between 0.636 inches and 0.652 inches

First Leg Slot Width:

Between 0.256 inches and 0.272 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.610 inches and 0.650 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.360 inches and 0.400 inches

First Leg Thickness:

Between 0.182 inches and 0.198 inches

Second Leg Thickness:

Between 0.182 inches and 0.198 inches

First Leg Width:

Between 7.734 inches and 7.770 inches

First Leg Distance Between First And Second Hole Centers Along Width:

Between 1.992 inches and 2.008 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

Between 2.480 inches and 2.520 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.480 inches and 0.520 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.480 inches and 0.520 inches

First Leg Distance Between Third And Fourth Hole Centers Along Width:

Between 1.992 inches and 2.008 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

5 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Cutout Length:

Between 2.480 inches and 2.520 inches

First Leg Cutout Width:

Between 3.980 inches and 4.020 inches

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.