

View Online at <https://aerobasegroup.com/nsn/5340-01-280-6869>

**Mounting Hole Type:**

Plain

**First Leg Length:**

3.005 inches

**Second Leg Length:**

5.345 inches

**Second Leg Width:**

3.560 inches

**First Leg Slot Length:**

0.750 inches

**First Leg Slot Width:**

0.438 inches

**Second Leg Hole Diameter:**

2.812 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.780 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.780 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

8.000 inches

**First Leg Distance Between Hole Centers Along Width:**

4.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.620 inches

**Second Leg End Radius:**

1.780 inches

**First Leg Style:**

Angle

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Second leg hole is flat on both sides; color green no. 383

**Material:**

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

**Material Specification:**

Astm a568, t3 assn standard all material responses or astm a568, t5 assn standard all material responses or astm a519 assn standard all material responses

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.