NSN 5340-01-280-6875

Angle Bracket - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5340-01-280-6875 | |
|---|--|
| Mounting Hole Type: | |
| Plain | |
| First Leg Length: | |
| Between 1.060 inches and 1.075 inches | |
| Second Leg Length: | |
| Between 1.610 inches and 1.625 inches | |
| Second Leg Width: | |
| 1.000 inches | |
| First Leg Hole Diameter: | |
| 0.469 inches | |
| Second Leg Hole Diameter: | |
| 0.203 inches | |
| Second Leg Distance From Edge To Hole Center Along Width: | |
| 0.500 inches | |
| Second Leg Distance From Edge To Hole Center Along Length: | |
| 0.300 inches | |
| First Leg Thickness: | |
| Between 0.0598 inches and 0.0747 inches | |
| Second Leg Thickness: | |
| Between 0.0598 inches and 0.0747 inches | |
| First Leg Width: | |
| 1.000 inches | |
| First Leg Distance From Edge To Hole Center Along Width: | |
| 0.500 inches | |
| First Leg Distance From Edge To Hole Center Along Length: | |
| 0.500 inches | |
| First Leg End Radius: | |
| 1.000 inches | |
| Second Leg End Radius: | |
| 1.000 inches | |
| First Leg Style: | |
| End radius | |
| First Leg Hole Arrangement Style: | |
| One hole | |
| Second Leg Style: | |
| End radius | |
| Second Leg Hole Arrangement Style: | |
| One hole | |
| Second Leg Relationship To First Leg: | |
| Not identical | |
| First Leg Angle: | |

90.0 degrees

NSN 5340-01-280-6875

Angle Bracket - Page 2 of 2



| Special Features: |
|---|
| Green, 383, mil-c-46168 or mil-c-53039 |
| Material: |
| Steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 |
| Surface Treatment: |
| Plastic polyurethane |
| Surface Treatment Specification: |
| Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig:

No

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.