

View Online at <https://aerobasegroup.com/nsn/5340-01-280-6954>

Cross Sectional Shape:

Flat

Hole Diameter:

Between 0.279 inches and 0.289 inches

Width:

9.218 inches

Edge Shape:

Rectangle, multi holes

Length:

10.218 inches

Corner Radius:

Between 1.016 inches and 1.036 inches

Hole Quantity Along Length:

6

Hole Quantity Along Width:

8

Distance Between Holes Along Length:

3.000 inches

Distance Between Holes Along Width:

1.500 inches and 1.500 inches and 3.000 inches

Distance Between Hole Centerline And First Hole Along Length:

1.312 inches

Distance Between Hole Centerline And First Hole Along Width:

1.812 inches

Distance From First Hole Centerline To End Along Length:

2.108 inches

Distance From First Hole Centerline To End Along Width:

1.608 inches

Body Thickness:

0.250 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

Special Features:

Two thd holes 0.190-24 unc-3b

Material:

Aluminum alloy 6061

Material Specification:

Alassoc a96061, t651 assn standard single material response or alassoc a96061, t6 assn standard single material response

Surface Treatment:

Anodize or chromate

Surface Treatment Specification:

Mil-a-8625, type 2, cl 1 military specification 1st treatment response or mil-c-5541, cl 1a military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-a-8625 spec.