

View Online at <https://aerobasegroup.com/nsn/5340-01-281-0929>

Mounting Hole Type:

Plain

First Leg Length:

1.000 inches

Second Leg Length:

2.000 inches

Second Leg Width:

2.000 inches

Second Leg End Width:

1.760 inches

First Leg Hole Diameter:

Between 0.168 inches and 0.174 inches

Second Leg Hole Diameter:

Between 0.143 inches and 0.149 inches

Second Leg Distance Between Upper Hole Centers Along Width:

0.875 inches

Second Leg Distance Between Lower Hole Centers Along Width:

1.406 inches

Second Leg Distance Between Hole Centers Along Length:

0.900 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.307 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.560 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

2.000 inches

First Leg End Width:

1.760 inches

First Leg Distance Between Hole Centers Along Width:

1.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.380 inches

First Leg Distance From Edge To Hole Center Along Length:

0.400 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Cutout Length:

0.750 inches

Second Leg Cutout Width:

1.120 inches

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

0.250 in. Bend r; not ch corner radii 0.120 in.; notch corners chamfered 0.120 in. By 45.0 deg

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t4 federal specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0