NSN 5340-01-281-5371

Mounting Bracket - Page 1 of 1

A042a0



View Online at https://aerobasegroup.com/nsn/5340-01-281-5371

F-16 c/d blk 40/60 Special Features: Fcorrosion resistant steel per ams 5629, passivate per qq-p-35, types 1, 2 or 3 after shot peen, 2.066 in. Min to 2.070 in. Maximum Ig, contains 4 holes through both walls, 0.077 in. Min to 0.082 in. Maximum diameter Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	End Application:
Fcorrosion resistant steel per ams 5629, passivate per qq-p-35, types 1, 2 or 3 after shot peen, 2.066 in. Min to 2.070 in. Maximum Ig, contains 4 holes through both walls, 0.077 in. Min to 0.082 in. Maximum diameter Shelf Life: N/a Unit Of Measure: Demilitarization: No	F-16 c/d blk 40/60
contains 4 holes through both walls, 0.077 in. Min to 0.082 in. Maximum diameter Shelf Life: N/a Unit Of Measure: Demilitarization: No	Special Features:
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Fcorrosion resistant steel per ams 5629, passivate per qq-p-35, types 1, 2 or 3 after shot peen, 2.066 in. Min to 2.070 in. Maximum Ig,
N/a Unit Of Measure: Demilitarization: No	contains 4 holes through both walls, 0.077 in. Min to 0.082 in. Maximum diameter
Unit Of Measure: Demilitarization: No	Shelf Life:
Demilitarization: No	N/a
Demilitarization: No	Unit Of Measure:
No	
	Demilitarization:
Fiig:	No
	Fiig: