

View Online at <https://aerobasegroup.com/nsn/5340-01-281-8426>

Mounting Hole Type:

Plain

First Leg Length:

1.620 inches

Second Leg Length:

1.920 inches

End Application:

Lau-105

First Leg Hole Diameter:

Between 0.191 inches and 0.196 inches

Second Leg Distance Between Hole Centers Along Width:

0.800 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.4100 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

Center Section Height:

Between 1.343 inches and 1.383 inches

Center Section Width:

1.360 inches

Center Section Thickness:

0.090 inches

First Leg Width:

1.6200 inches

First Leg End Width:

1.1200 inches

First Leg Distance Between Hole Centers Along Width:

0.800 inches

First Leg Distance From Edge To Hole Center Along Length:

0.4000 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

1st leg has keyway opening oa lg 0.685 in., keyway width 0.145 in., lg 0.200 in.; 2nd leg has 2 openings 0.622 in. To 0.630 in. Lg & 0.562 in. To 0.567 in. Width, dist from edge to opening cntr along width 0.920 in. W/dist from edge to cntr along lg 0.810 in.

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/4 t62 federal specification single material response

Surface Treatment Specification:

Mil-std-1516 code as military standard single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-1516 spec.