

View Online at <https://aerobasegroup.com/nsn/5340-01-282-2878>

**Cross Sectional Shape:**

Flat

**Edge Shape:**

Rectangle, four holes

**Body Thickness:**

0.040 inches

**Securing Device Type:**

Threaded fastener

**End Application:**

An/alq-161; b1-b acft

**Features Provided:**

Special marking

**Special Features:**

Item requires 28 6-32 unc-2b thd through & spotfaced 0.344 in. Diameter flush with maximum depth of 0.010 in., 1 extrusion p/n/ 441082-100, 1 extrusion p/n 441082-101, 30 screws p/n 411239-2, 30 lock washers p/n ms35338-136, 1 extrusion p/n 441082-103, 1 extrusion p/n 441082-104 & 30 flat washers p/n nas620c6

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 federal specification single material response

**Surface Treatment:**

Chromate and primer epoxy-polyamide

**Surface Treatment Specification:**

Mil-c-5541, cl 3 military specification 1st treatment response and mil-p-23377 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531c0

**Mil-std (military Standard):**

Mil-c-5541 spec.