

View Online at <https://aerobasegroup.com/nsn/5340-01-282-5709>

**Cross Sectional Shape:**

Square or rectangular recess

**Hole Diameter:**

Between 0.198 inches and 0.204 inches

**Width:**

7.500 inches

**Flange Thickness:**

Between 0.110 inches and 0.140 inches

**Edge Shape:**

Rectangle, multi holes

**Length:**

Between 13.219 inches and 13.281 inches

**Inside Width:**

Between 6.500 inches and 6.562 inches

**Inside Length:**

Between 11.625 inches and 11.687 inches

**Corner Radius:**

Between 0.673 inches and 0.703 inches

**Hole Quantity Along Length:**

10

**Hole Quantity Along Width:**

8

**Distance Between Holes Along Length:**

3.500 inches and 1.750 inches and 1.750 inches and 3.500 inches

**Distance Between Holes Along Width:**

1.438 inches and 1.750 inches and 1.750 inches

**Distance Between Hole Centerline And First Hole Along Length:**

1.063 inches

**Distance Between Hole Centerline And First Hole Along Width:**

1.125 inches

**Distance From First Hole Centerline To End Along Length:**

Between 1.359 inches and 1.389 inches

**Distance From First Hole Centerline To End Along Width:**

Between 1.422 inches and 1.452 inches

**First Recess Inside Height:**

Between 5.594 inches and 5.656 inches

**Inside Corner Radius:**

0.125 inches

**Body Thickness:**

Between 0.110 inches and 0.140 inches

**Securing Device Type:**

Special

**Mounting Opening Shape Style:**

Unthreaded hole

**Special Features:**

4 0.227 in. Min, 0.233 in. Maximum diameter holes; 18 holes are 82.0 degrees by 0.390 in. Diameter countersunk

**Material:**

Aluminum alloy 5052

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A531c0

**Mil-std (military Standard):**

Mil-c-5541 spec.