

View Online at <https://aerobasegroup.com/nsn/5340-01-282-5709>

Cross Sectional Shape:

Square or rectangular recess

Hole Diameter:

Between 0.198 inches and 0.204 inches

Width:

7.500 inches

Flange Thickness:

Between 0.110 inches and 0.140 inches

Edge Shape:

Rectangle, multi holes

Length:

Between 13.219 inches and 13.281 inches

Inside Width:

Between 6.500 inches and 6.562 inches

Inside Length:

Between 11.625 inches and 11.687 inches

Corner Radius:

Between 0.673 inches and 0.703 inches

Hole Quantity Along Length:

10

Hole Quantity Along Width:

8

Distance Between Holes Along Length:

3.500 inches and 1.750 inches and 1.750 inches and 3.500 inches

Distance Between Holes Along Width:

1.438 inches and 1.750 inches and 1.750 inches

Distance Between Hole Centerline And First Hole Along Length:

1.063 inches

Distance Between Hole Centerline And First Hole Along Width:

1.125 inches

Distance From First Hole Centerline To End Along Length:

Between 1.359 inches and 1.389 inches

Distance From First Hole Centerline To End Along Width:

Between 1.422 inches and 1.452 inches

First Recess Inside Height:

Between 5.594 inches and 5.656 inches

Inside Corner Radius:

0.125 inches

Body Thickness:

Between 0.110 inches and 0.140 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

Special Features:

4 0.227 in. Min, 0.233 in. Maximum diameter holes; 18 holes are 82.0 degrees by 0.390 in. Diameter countersunk

Material:

Aluminum alloy 5052

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-c-5541 spec.