

View Online at <https://aerobasegroup.com/nsn/5340-01-282-8230>

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

1.000 inches

Second Leg Width:

0.812 inches

Second Leg Corner Radius:

0.062 inches

First Leg Slot Length:

0.438 inches

First Leg Slot Width:

Between 0.169 inches and 0.179 inches

Second Leg Hole Diameter:

Between 0.123 inches and 0.130 inches

Second Leg Distance Between Hole Centers Along Length:

0.445 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.130 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.139 inches

First Leg Thickness:

Between 0.110 inches and 0.140 inches

Second Leg Thickness:

Between 0.110 inches and 0.140 inches

First Leg Width:

0.500 inches

First Leg Corner Radius:

0.062 inches

First Leg Distance From Edge To Hole Center Along Width:

0.248 inches

First Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Temper t5; color iridescent bronze

Material:

Aluminum alloy 6063

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.