

View Online at <https://aerobasegroup.com/nsn/5340-01-283-1230>

First Leg Length:

0.080 inches

Second Leg Length:

2.500 inches

Reinforcement Method (non-core):

Turned edge second leg

Second Leg Width:

Between 3.100 inches and 3.140 inches

First Leg Slot Length:

0.500 inches

First Leg Slot Width:

0.250 inches

Second Leg Distance Between Hole Centers Along Width:

1.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.743 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.745 inches

Second Leg Slot Length:

0.750 inches

Second Leg Slot Width:

0.250 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

1.750 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.625 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

0.625 inches

First Leg Distance From Edge To Hole Center Along Width:

0.253 inches

First Leg Distance From Edge To Hole Center Along Length:

0.360 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

3 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 302

Material Specification:

Qq-s-763, cond a federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0