

View Online at <https://aerobasegroup.com/nsn/5340-01-283-3645>

Cross Sectional Shape:

Square or rectangular recess

Hole Diameter:

0.290 inches

Width:

6.120 inches

Flange Thickness:

0.380 inches

Edge Shape:

Rectangle, multi holes

Length:

8.260 inches

Inside Width:

Between 4.090 inches and 4.150 inches

Inside Length:

Between 6.200 inches and 6.290 inches

Corner Radius:

0.380 inches

Hole Quantity Along Length:

8

Hole Quantity Along Width:

6

Distance Between Holes Along Length:

1.940 inches

Distance Between Holes Along Width:

1.820 inches

Distance Between Hole Centerline And First Hole Along Length:

0.920 inches

Distance Between Hole Centerline And First Hole Along Width:

0.940 inches

Distance From First Hole Centerline To End Along Length:

1.220 inches

Distance From First Hole Centerline To End Along Width:

1.240 inches

First Recess Inside Height:

5.820 inches

Inside Corner Radius:

0.250 inches

Body Thickness:

0.380 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

Special Features:

One external reinforcing rib centered along length 0.380 in. Thk; spot face all mtg holes 0.562 in. Dia; one threaded hole in side wall

0.875-14unf-2b

Material:

Copper alloy

Material Specification:

Mil-b-24480 military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A531c0

Mil-std (military Standard):

Mil-b-24480 spec.