

View Online at <https://aerobasegroup.com/nsn/5340-01-285-7057>

Cross Sectional Shape:

Flat, square or rectangular rib reinforced

Hole Diameter:

Between 0.168 inches and 0.174 inches

Width:

1.325 inches

Flange Thickness:

0.062 inches

Edge Shape:

Rectangle, multi holes

Length:

7.000 inches

Hole Quantity Along Length:

2

Distance Between Holes Along Length:

6.608 inches

Distance From First Hole Centerline To End Along Length:

0.196 inches

Distance From First Hole Centerline To End Along Width:

0.663 inches

Body Thickness:

0.250 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

Special Features:

Zrectangular groove 6.248 in. Lg o/a by 1.200 in. W o/a, 0.057 in. Min 0.067 in. Maximum groove w; 0.025 in. Main 0.035 in. Maximum groove dp; molded in place gasket of electrically conductive elastomer in groove, 717806052, martin marietta corp

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11-t6 federal specification single material response

Surface Treatment:

Nickel

Surface Treatment Specification:

717806000, code 3405, martin marietta corporation mfr ref single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A531c0