

View Online at <https://aerobasegroup.com/nsn/5340-01-285-7057>

**Cross Sectional Shape:**

Flat, square or rectangular rib reinforced

**Hole Diameter:**

Between 0.168 inches and 0.174 inches

**Width:**

1.325 inches

**Flange Thickness:**

0.062 inches

**Edge Shape:**

Rectangle, multi holes

**Length:**

7.000 inches

**Hole Quantity Along Length:**

2

**Distance Between Holes Along Length:**

6.608 inches

**Distance From First Hole Centerline To End Along Length:**

0.196 inches

**Distance From First Hole Centerline To End Along Width:**

0.663 inches

**Body Thickness:**

0.250 inches

**Securing Device Type:**

Special

**Mounting Opening Shape Style:**

Unthreaded hole

**Special Features:**

Rectangular groove 6.248 in. Lg o/a by 1.200 in. W o/a, 0.057 in. Min 0.067 in. Maximum groove w; 0.025 in. Main 0.035 in. Maximum groove dp; molded in place gasket of electrically conductive elastomer in groove, 717806052, martin marietta corp

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11-t6 federal specification single material response

**Surface Treatment:**

Nickel

**Surface Treatment Specification:**

717806000, code 3405, martin marietta corporation mfr ref single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A531c0