

View Online at <https://aerobasegroup.com/nsn/5340-01-285-9374>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.750 inches

**Second Leg Length:**

1.000 inches

**Second Leg Width:**

0.812 inches

**Second Leg Corner Radius:**

0.062 inches

**First Leg Slot Length:**

0.438 inches

**First Leg Slot Width:**

Between 0.169 inches and 0.179 inches

**Second Leg Hole Diameter:**

Between 0.123 inches and 0.130 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.445 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.682 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.139 inches

**First Leg Thickness:**

Between 0.110 inches and 0.140 inches

**Second Leg Thickness:**

Between 0.110 inches and 0.140 inches

**First Leg Width:**

0.500 inches

**First Leg Corner Radius:**

0.062 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.248 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.312 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Temper t5

**Material:**

Aluminum alloy 6063

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.