# NSN 5340-01-286-0901

Angle Bracket - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5340-01-286-0901



Mounting Hole Type:
Plain

- First Leg Length:
- 1.500 inches
- Second Leg Length:
- 2.000 inches
- Second Leg Width:
- 22.800 inches
- Second Leg End Width:

20.800 inches

- First Leg Hole Diameter:
- 0.312 inches
- Second Leg Hole Diameter:

#### 0.312 inches

Second Leg Distance Between Hole Centers Along Width:

#### 16.000 inches

- Second Leg Distance Between Hole Centers Along Length:
- 0.800 inches
- Second Leg Distance From Edge To Hole Center Along Width:
- 6.050 inches
- Second Leg Distance From Edge To Hole Center Along Length:
- 0.450 inches
- First Leg Thickness:
- 0.187 inches
- Second Leg Thickness:
- 0.187 inches
- First Leg Width:

22.800 inches

First Leg Distance Between Hole Centers Along Width:

17.300 inches

First Leg Distance Between First And Second Hole Centers Along Width:

4.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

9.300 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

- First Leg Distance From Edge To Hole Center Along Length:
- 0.740 inches
- First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

# NSN 5340-01-286-0901

Angle Bracket - Page 2 of 2



#### Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

### First Leg Angle:

90.0 degrees

## **Special Features:**

First leg has one additional hole 0.234 in. Diameter on same centerline as other holes and spaced 20.000 in. From first hole; left hand

# design

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/8, t6 federal specification single material response

Surface Treatment:

Primer

## Surface Treatment Specification:

Mil-f-14072-+513.1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-f-14072- spec.