NSN 5340-01-286-9845

Access Cover - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-286-9845

Hole Diameter: .0.014 inches Width: 4.114 inches Edge Shape: Rectangle, multi holes Length: 7.409 inches Hole Quantity Along Length: 8 Hole Quantity Along Width: 8 Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantin rigt pod Features Provided: Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa Ig 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Altuminum alloy 6061 Material: Altuminum alloy 6061 Material Specification: Qq-a-250/11 1651 federal specification single material response Shelf Life: N/a Unit Of Measure: — Demilitarization: Yes - demill/mlii	Cross Sectional Shape:
With: 4.114 inches Edge Shape: Rectangle, multi holes Length: 7.409 inches Hole Quantity Along Length: 8 Hole Quantity Along Width: 8 Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantim tgt pod Features Provided: Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa Ig 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: Na Unit Of Measure:	Flat
Width: 4.114 inches Edge Shape: Rectangle, multi holes Length: 7.409 inches Hole Quantity Along Length: 8 Hole Quantity Along Width: 8 Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantirn 1gt pod Features Provided: Special marking Special rearking Special rearking Special rearking Lantirn 1gt pod Features Provided: Special rearking Special rearkin	Hole Diameter:
4.114 inches Edge Shape: Rectangle, multi holes Length: 7.409 inches Hole Quantity Along Length: 8 Hole Quantity Along Width: 8 Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantin tgt pod Features Provided: Special marking Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 1651 federal specification single material response Sheft Life: N/a Unit Of Measure:	0.014 inches
Edge Shape: Rectangle, multi holes Length: 7.409 inches Hole Quantity Along Length: 8 Hole Quantity Along Width: 8 Securing Device Type: Special Mounting Opening Shape Style: Unithreaded hole End Application: Lantim tgt pod Features Provided: Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 (651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Width:
Rectangle, multi holes Length: 7.409 inches Hole Quantity Along Length: 8 Hole Quantity Along Width: 8 Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantim tgt pod Features Provided: Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa Ig 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 (651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	4.114 inches
Length: 7.409 inches Hole Quantity Along Length: 8 Hole Quantity Along Width: 8 Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantirn tgt pod Features Provided: Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa Ig 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Materials Specification: Qq-a-250/11 1651 federal specification single material response Shelf Life: N/a Unit Of Measure: — Demilitarization: Yes - demil/mli	Edge Shape:
7.409 inches Hole Quantity Along Length: 8 Hole Quantity Along Width: 8 Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantim tgt pod Features Provided: Special marking Special Features: Iltem requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0815 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Rectangle, multi holes
Hole Quantity Along Length: 8 Hole Quantity Along Width: 8 Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantim tgt pod Features Provided: Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa Ig 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: — Demilitarization: Yes - demil/mli	Length:
Hole Quantity Along Width: 8 Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantim tg pod Features Provided: Special marking Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Altuminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: —— Demilitarization: Yes - demil/mli	7.409 inches
Hole Quantity Along Width: 8 Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantim tot pod Features Provided: Special marking Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 1651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Hole Quantity Along Length:
Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantim tgt pod Features Provided: Special marking Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 1651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	8
Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantim tgt pod Features Provided: Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 1651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Hole Quantity Along Width:
Special Mounting Opening Shape Style: Unthreaded hole End Application: Lantirr tgt pod Features Provided: Special marking Special Features: Ittem requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	8
Mounting Opening Shape Style: Unthreaded hole End Application: Lantim tgt pod Features Provided: Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Securing Device Type:
Unthreaded hole End Application: Lantirn tgt pod Features Provided: Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: — Demilitarization: Yes - demil/mli	Special
End Application: Lantim tgt pod Features Provided: Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Mounting Opening Shape Style:
Lantirn tgt pod Features Provided: Special marking Special Features: Ittem requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Unthreaded hole
Features Provided: Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	End Application:
Special marking Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Lantirn tgt pod
Special Features: Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Features Provided:
Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X 45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 1651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Special marking
45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 & ms21209c0415 Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Special Features:
Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Item requires 2 tapered guide pins, dia 0.1870 to 0.1872 in. P/n 717513176-002, pins oa lg 0.875 in., chamfered 0.020 in. Porm 0.010 in. X
Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	45 degrees porm 5 degrees & has 0.040 in. Porm 0.020 in. Spher radius; also requires 16 coarse & f insert screws p/n ms21209c0615 &
Aluminum alloy 6061 Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	ms21209c0415
Material Specification: Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Material:
Qq-a-250/11 t651 federal specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Aluminum alloy 6061
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Material Specification:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Qq-a-250/11 t651 federal specification single material response
Unit Of Measure: Demilitarization: Yes - demil/mli	Shelf Life:
 Demilitarization: Yes - demil/mli	N/a
Yes - demil/mli	Unit Of Measure:
Yes - demil/mli	
	Demilitarization:
Eija:	Yes - demil/mli
riig.	Fiig:
A531c0	A531c0