

View Online at <https://aerobasegroup.com/nsn/5340-01-287-8852>

Cross Sectional Shape:

Flat

Hole Diameter:

Between 0.311 inches and 0.318 inches

Width:

11.625 inches

Edge Shape:

Rectangle, multi holes

Length:

17.500 inches

Corner Radius:

Between 0.219 inches and 0.281 inches

Hole Quantity Along Length:

2

Hole Quantity Along Width:

4

Distance Between Holes Along Length:

6.250 inches

Distance Between Holes Along Width:

11.000 inches

Distance From First Hole Centerline To End Along Length:

2.500 inches

Distance From First Hole Centerline To End Along Width:

0.312 inches

Body Thickness:

0.125 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

Special Features:

Has two 0.232 in. Min, 0.240 in. Maximum diameter holes; consists of one 2.250 in. Min, 2.750 in. Maximum thk by 9.750 in. Min, 10.250 in. Maximum w by 16.250 in. Min, 16.750 in. Maximum lg polyurethane foam block and six fasteners

Material:

Aluminum alloy 6061

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1, cl 2 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A531c0

Mil-std (military Standard):

Mil-a-8625 spec.