

View Online at <https://aerobasegroup.com/nsn/5340-01-287-9229>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.500 inches

**Second Leg Length:**

2.000 inches

**Second Leg Width:**

19.250 inches

**First Leg Hole Diameter:**

0.312 inches

**Second Leg Hole Diameter:**

0.312 inches

**Second Leg Distance Between Hole Centers Along Width:**

16.000 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.800 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.450 inches

**First Leg Thickness:**

0.188 inches

**Second Leg Thickness:**

0.188 inches

**First Leg Width:**

19.250 inches

**First Leg Distance Between Hole Centers Along Width:**

15.000 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

4.000 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

7.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

3.460 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.750 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Four holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-200/8, t6 federal specification single material response

**Surface Treatment:**

Primer

**Surface Treatment Specification:**

Mil-f-14072-+513.1 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-f-14072- spec.