

View Online at <https://aerobasegroup.com/nsn/5340-01-288-2127>

Mounting Hole Type:

Plain

First Leg Length:

1.125 inches

Second Leg Length:

1.455 inches

Second Leg Width:

5.500 inches

First Leg Hole Diameter:

0.156 inches

Second Leg Hole Diameter:

0.406 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.390 inches and 0.510 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

5.500 inches

First Leg Distance Between Upper Hole Centers Along Width:

1.500 inches

First Leg Distance Between Lower Hole Centers Along Width:

4.500 inches

First Leg Distance Between Hole Centers Along Length:

Between 0.320 inches and 0.440 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.360 inches

Second Leg End Radius:

Between 0.390 inches and 0.510 inches

First Leg Style:

Square

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6010

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.