

View Online at <https://aerobasegroup.com/nsn/5340-01-288-2132>

**Mounting Hole Type:**

Plain

**First Leg Length:**

3.510 inches

**Second Leg Length:**

4.500 inches

**First Leg Hole Diameter:**

0.406 inches

**Second Leg Hole Diameter:**

0.531 inches

**Second Leg Distance Between Hole Centers Along Length:**

2.560 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.880 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**Center Section Height:**

1.250 inches

**Center Section Width:**

3.000 inches

**Center Section Thickness:**

0.250 inches

**First Leg Width:**

3.000 inches

**First Leg End Width:**

1.000 inches

**First Leg Distance Between Hole Centers Along Length:**

1.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

**Material Specification:**

Qq-s-698 temp 3-5 federal specification all material responses or sae j403 temp 2-5 assn standard all material responses

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.