

View Online at <https://aerobasegroup.com/nsn/5340-01-288-2132>

Mounting Hole Type:

Plain

First Leg Length:

3.510 inches

Second Leg Length:

4.500 inches

First Leg Hole Diameter:

0.406 inches

Second Leg Hole Diameter:

0.531 inches

Second Leg Distance Between Hole Centers Along Length:

2.560 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.880 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

Center Section Height:

1.250 inches

Center Section Width:

3.000 inches

Center Section Thickness:

0.250 inches

First Leg Width:

3.000 inches

First Leg End Width:

1.000 inches

First Leg Distance Between Hole Centers Along Length:

1.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

Material Specification:

Qq-s-698 temp 3-5 federal specification all material responses or sae j403 temp 2-5 assn standard all material responses

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.