

View Online at <https://aerobasegroup.com/nsn/5340-01-288-4557>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.505 inches

**Second Leg Length:**

2.620 inches

**Second Leg Width:**

2.500 inches

**First Leg Hole Diameter:**

0.531 inches

**Second Leg Hole Diameter:**

0.343 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.500 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**Center Section Height:**

1.685 inches

**Center Section Width:**

2.500 inches

**Center Section Thickness:**

0.125 inches

**First Leg Width:**

2.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015

**Material Specification:**

Astm a366 assn standard all material responses

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.