NSN 5340-01-288-9210

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-288-9210 **Mounting Hole Type:** Plain First Leg Length: 5.730 inches Second Leg Length: 6.380 inches Second Leg Width: 1.500 inches First Leg Hole Diameter: Between 0.534 inches and 0.547 inches Second Leg Hole Diameter: 0.406 inches Second Leg Distance Between Hole Centers Along Length: 1.500 inches Second Leg Distance From Edge To Hole Center Along Width: 0.620 inches **Second Leg Distance From Edge To Hole Center Along Length:** 0.500 inches First Leg Thickness: 0.250 inches Second Leg Thickness: 0.250 inches **Center Section Height:** 8.910 inches **Center Section Width:** 1.500 inches **Center Section Thickness:** 0.250 inches First Leg Width: 1.500 inches First Leg Distance Between Hole Centers Along Length: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.620 inches First Leg Distance From Edge To Hole Center Along Length: 0.700 inches First Leg Style: Extended flat First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

NSN 5340-01-288-9210

Double Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
Second Leg Angle:
90.0 degrees
Special Features:
Paint color green
Material:
Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or
steel comp 1020
Material Specification:
Astm a108 assn standard all material responses or astm a576 assn standard all material responses or astm a635 assn standard all material
responses
Surface Treatment:
Paint
Surface Treatment Specification:
Mil-c-46168, n0. 383 military specification single treatment response
Style Designator:
Adjacent angles
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-46168 spec.