

View Online at <https://aerobasegroup.com/nsn/5340-01-288-9445>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.750 inches

**Second Leg Length:**

0.800 inches

**Second Leg Width:**

1.188 inches

**Second Leg Corner Radius:**

0.300 inches

**First Leg Hole Diameter:**

Between 0.129 inches and 0.134 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.438 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.300 inches

**Second Leg Slot Length:**

0.499 inches

**Second Leg Slot Width:**

0.224 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

1.000 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Incl cres clip nut

**Material:**

Titanium alloy

**Material Specification:**

Mil-t-9046, comp cp-1 military specification 1st material response or mil-t-9046, comp cp-3 military specification 2nd material response or ams 4901 assn standard 3rd material response or ams 4902 assn standard 4th material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-t-9046 spec.