

View Online at <https://aerobasegroup.com/nsn/5340-01-289-5028>

Mounting Hole Type:

Plain

First Leg Length:

2.505 inches

Second Leg Length:

3.505 inches

First Leg Hole Diameter:

0.173 inches

Second Leg Distance Between Hole Centers Along Width:

1.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.570 inches

Second Leg Slot Length:

0.650 inches

Second Leg Slot Width:

0.406 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

0.940 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.320 inches

First Leg Distance Between Hole Centers Along Length:

0.480 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.440 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

Material Specification:

Astm a568 assn standard all material responses

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.