

View Online at <https://aerobasegroup.com/nsn/5340-01-289-7855>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.000 inches

**Second Leg Length:**

2.750 inches

**Second Leg Width:**

2.250 inches

**Second Leg Corner Radius:**

0.250 inches

**First Leg Hole Diameter:**

0.281 inches

**Second Leg Hole Diameter:**

1.150 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.120 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Thickness:**

0.119 inches

**Second Leg Thickness:**

0.119 inches

**First Leg Width:**

2.250 inches

**First Leg Corner Radius:**

0.120 inches

**First Leg Distance Between Hole Centers Along Width:**

1.250 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Color green

**Material:**

Steel comp 1009 or steel comp 1137 or steel uns k01507 or steel uns k02500

**Material Specification:**

Astm a569 assn standard 1st material response or astm a366 assn standard 1st material response or astm a109 assn standard 2nd material response or astm a109 assn standard 3rd material response or astm a109 assn standard 4th material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.