

View Online at <https://aerobasegroup.com/nsn/5340-01-289-8503>

**End Application:**

An/aps-133

**Special Features:**

Item has multiple holes, 4 marked 'a' w/dia 0.099 to 0.103 in. By which bearing pad is clamped into position via pilot holes & csk 100 degrees porm 2 degrees to diameter of 0.120 in. Farside, 2 holes marked 'b' w/dia 0.127 to 0.131 in.& csk 100 degrees porm 2 degrees to diameter of 0.230 in. Farside; assembled item consists of a bearing pad bracket p/n 238164-0501, which requires 1 bearing pad p/n2035406-0001, 4 100 degrees flat hd rivets 0.094 in. By o.250 in., p/n 37004-2210, 1 bracket mtg bearing pad p/n 2035407-0001, 1 angle bracket p/n 2038450-001 & 2 100 degrees flat hd rivets 0.1215 in. Diameter by 0.250 in. Lg p/n 37004-3322 or ms20427-f44; includes bearing p/n 2068279-0701 & captive screw p/n 46067-10a3; captive screw to be clinched in place on bracket assembly after bearing is inserted in place

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0