

View Online at <https://aerobasegroup.com/nsn/5340-01-291-0775>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.443 inches

**Second Leg Length:**

2.483 inches

**Second Leg Width:**

0.320 inches

**First Leg Hole Diameter:**

0.125 inches

**Second Leg Hole Diameter:**

0.140 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.750 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.160 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.182 inches

**Second Leg Distance Between First And Second Hole Centers Along Length:**

0.312 inches

**Second Leg Distance Between Second And Third Hole Centers Along Length:**

1.125 inches

**First Leg Thickness:**

Between 0.059 inches and 0.067 inches

**Second Leg Thickness:**

Between 0.059 inches and 0.067 inches

**First Leg Width:**

0.320 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.160 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.200 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Two center holes in second leg are 0.093 in. Diameter countersunk opposite side to 0.177 in. Dia

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8, h32 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.