

View Online at <https://aerobasegroup.com/nsn/5340-01-292-1462>

**First Leg Length:**

5.000 inches

**Second Leg Length:**

5.620 inches

**Reinforcement Method (non-core):**

Gusset both sides

**Second Leg Width:**

2.250 inches

**First Leg Slot Length:**

1.250 inches

**First Leg Slot Width:**

0.310 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.000 inches

**Second Leg Distance Between Hole Centers Along Length:**

2.750 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.585 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**Second Leg Slot Length:**

0.430 inches

**Second Leg Slot Width:**

0.250 inches

**First Leg Thickness:**

0.0641 inches

**Second Leg Thickness:**

0.0641 inches

**First Leg Width:**

2.250 inches

**First Leg Distance Between Hole Centers Along Width:**

1.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.370 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.875 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

4 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Two triangular gussets 1.620 in. Lg by 0.870 in. W by 0.064 in. Thk; mtg slots in second leg oriented w/longitudinal axis perpendicular to sides; aluminum temper t6

**Material:**

Aluminum alloy 6061

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Tt-p-1757, color yellow federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0