

View Online at <https://aerobasegroup.com/nsn/5340-01-292-1462>

First Leg Length:

5.000 inches

Second Leg Length:

5.620 inches

Reinforcement Method (non-core):

Gusset both sides

Second Leg Width:

2.250 inches

First Leg Slot Length:

1.250 inches

First Leg Slot Width:

0.310 inches

Second Leg Distance Between Hole Centers Along Width:

1.000 inches

Second Leg Distance Between Hole Centers Along Length:

2.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.585 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

Second Leg Slot Length:

0.430 inches

Second Leg Slot Width:

0.250 inches

First Leg Thickness:

0.0641 inches

Second Leg Thickness:

0.0641 inches

First Leg Width:

2.250 inches

First Leg Distance Between Hole Centers Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.370 inches

First Leg Distance From Edge To Hole Center Along Length:

0.875 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

4 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Two triangular gussets 1.620 in. Lg by 0.870 in. W by 0.064 in. Thk; mtg slots in second leg oriented w/longitudinal axis perpendicular to sides; aluminum temper t6

Material:

Aluminum alloy 6061

Surface Treatment:

Chromate

Surface Treatment Specification:

Tt-p-1757, color yellow federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0