

View Online at <https://aerobasegroup.com/nsn/5340-01-292-1463>

Mounting Hole Type:

Plain

First Leg Length:

Between 0.970 inches and 1.030 inches

Second Leg Length:

Between 2.720 inches and 2.780 inches

Second Leg Width:

Between 1.850 inches and 1.910 inches

First Leg Hole Diameter:

Between 0.170 inches and 0.178 inches

Second Leg Hole Diameter:

Between 0.201 inches and 0.209 inches

Second Leg Distance Between Hole Centers Along Width:

1.250 inches

Second Leg Distance Between Hole Centers Along Length:

1.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.315 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.305 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

Between 1.850 inches and 1.910 inches

First Leg Distance Between Upper Hole Centers Along Width:

1.375 inches

First Leg Distance Between Lower Hole Centers Along Width:

0.750 inches

First Leg Distance Between Hole Centers Along Length:

0.312 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.312 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.220 inches and 0.280 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

0.985 in. Min and 1.015 in. Maximum hole diameter center section second leg

Material:

Aluminum alloy 6061

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.