

View Online at <https://aerobasegroup.com/nsn/5340-01-292-2486>

Mounting Hole Type:

Plain

First Leg Length:

1.500 inches

Second Leg Length:

2.000 inches

Second Leg Width:

2.500 inches

Second Leg End Width:

2.120 inches

First Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Hole Diameter:

Between 0.184 inches and 0.194 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.906 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

0.906 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.340 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.630 inches

First Leg Thickness:

0.190 inches

Second Leg Thickness:

0.190 inches

Center Section Height:

3.380 inches

Center Section Width:

2.500 inches

Center Section Thickness:

0.190 inches

First Leg Width:

2.500 inches

First Leg Distance Between Hole Centers Along Width:

1.812 inches

First Leg Distance From Edge To Hole Center Along Width:

0.340 inches

First Leg Distance From Edge To Hole Center Along Length:

0.430 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

Second leg, ctr hole 0.742 in. Min, 0.758 in. Max

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.