NSN 5340-01-292-2487

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-292-2487

| Manusting Hale Time. |
|---|
| Mounting Hole Type: |
| Plain |
| First Leg Length: |
| 0.340 inches |
| Second Leg Length: |
| 0.340 inches |
| First Leg Thickness: |
| 0.090 inches |
| Second Leg Thickness: |
| 0.090 inches |
| Center Section Height: |
| 2.370 inches |
| Center Section Width: |
| 16.380 inches |
| Center Section Thickness: |
| 0.090 inches |
| First Leg Width: |
| 16.380 inches |
| First Leg Style: |
| Square |
| First Leg Hole Arrangement Style: |
| No hole |
| Second Leg Relationship To First Leg: |
| Identical |
| First Leg Angle: |
| 90.0 degrees |
| Second Leg Angle: |
| 90.0 degrees |
| Special Features: |
| Holes located in ctr section |
| Material: |
| Aluminum alloy 6061 or aluminum alloy 5052 |
| Material Specification: |
| Qq-a-250/11, temper o federal specification 1st material response or qq-a-250/8, temper o federal specification 2nd material response |
| Surface Treatment: |
| Chromate |
| Surface Treatment Specification: |
| Mil-c-5541 military specification single treatment response |
| Style Designator: |
| Adjacent angles |
| Shelf Life: |
| N/a |

NSN 5340-01-292-2487

Double Angle Bracket - Page 2 of 2



| | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.