

View Online at <https://aerobasegroup.com/nsn/5340-01-292-5399>

Mounting Hole Type:

Plain and threaded

First Leg Length:

1.750 inches

Second Leg Length:

7.000 inches

Second Leg Width:

3.000 inches

Second Leg End Width:

6.000 inches

First Leg Hole Diameter:

0.500 inches

Second Leg Distance Between Hole Centers Along Width:

3.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

2.250 inches

Second Leg Slot Length:

1.812 inches

Second Leg Slot Width:

0.625 inches

First Leg Thickness:

0.750 inches

Second Leg Thickness:

0.500 inches

First Leg Width:

3.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg chamfered 0.250 in. By 45 deg

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-250/6 h321 or h323 federal specification 1st material response or qq-a-200/4 h111 federal specification 1st material response or qq-a-250/7 h32 federal specification 2nd material response or qq-a-200/5 h111 federal specification 2nd material response

Surface Treatment:

Paint

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0