

View Online at <https://aerobasegroup.com/nsn/5340-01-295-1088>

Mounting Hole Type:

Plain

First Leg Length:

Between 3.190 inches and 3.310 inches

Second Leg Length:

Between 6.940 inches and 7.060 inches

Reinforcement Method (non-core):

Gusset both legs

Second Leg Width:

1.250 inches

Second Leg End Width:

0.750 inches

First Leg Slot Length:

0.530 inches

First Leg Slot Width:

0.406 inches

Second Leg Hole Diameter:

0.406 inches

Second Leg Distance Between Hole Centers Along Length:

2.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

1.250 inches

First Leg End Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.625 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.440 inches and 0.560 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Material:

Steel

Material Specification:

Astm a36 assn standard single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.