

View Online at <https://aerobasegroup.com/nsn/5340-01-295-1088>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 3.190 inches and 3.310 inches

**Second Leg Length:**

Between 6.940 inches and 7.060 inches

**Reinforcement Method (non-core):**

Gusset both legs

**Second Leg Width:**

1.250 inches

**Second Leg End Width:**

0.750 inches

**First Leg Slot Length:**

0.530 inches

**First Leg Slot Width:**

0.406 inches

**Second Leg Hole Diameter:**

0.406 inches

**Second Leg Distance Between Hole Centers Along Length:**

2.250 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

1.250 inches

**First Leg End Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.625 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.440 inches and 0.560 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**First Leg Chamfer Angle:**

45.0 degrees

**Second Leg Chamfer Angle:**

45.0 degrees

**Material:**

Steel

**Material Specification:**

Astm a36 assn standard single material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.