## NSN 5340-01-296-2085



Angle Bracket - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5340-01-296-2085 **Mounting Hole Type:** Plain and countersunk First Leg Length: 1.000 inches Second Leg Length: 2.000 inches Second Leg Width: 2.000 inches First Leg Hole Diameter: Between 0.216 inches and 0.223 inches Second Leg Hole Diameter: 0.625 inches Second Leg Distance From Edge To Hole Center Along Width: 1.000 inches **Second Leg Distance From Edge To Hole Center Along Length:** 0.500 inches First Leg Thickness: 0.125 inches Second Leg Thickness: 0.125 inches First Leg Width: 2.000 inches First Leg Distance Between Hole Centers Along Width: 1.200 inches First Leg Distance From Edge To Hole Center Along Width: 0.400 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square Second Leg Hole Arrangement Style: One hole Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees

Color gray

**Special Features:** 

## NSN 5340-01-296-2085

Angle Bracket - Page 2 of 2

Mil-c-83286 spec.



| Material:  |
|--|
| Aluminum alloy 6063  |
| Material Specification:  |
| Qq-a-200/9, t52 federal specification single material response |
| Surface Treatment:   |
| Plastic polyurethane   |
| Surface Treatment Specification:                               |
| Mil-c-83286 military specification single treatment response   |
| Style Designator:  |
| Angle  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A042a0   |
| Mil-std (military Standard):                                   |