## NSN 5340-01-296-2086

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-296-2086

**Mounting Hole Type:** Plain First Leg Length: 1.000 inches Second Leg Length: 2.500 inches Second Leg Width: 2.750 inches First Leg Hole Diameter: Between 0.217 inches and 0.222 inches Second Leg Hole Diameter: Between 0.180 inches and 0.185 inches Second Leg Distance Between Hole Centers Along Width: 0.312 inches Second Leg Distance Between Hole Centers Along Length: 1.500 inches Second Leg Distance From Edge To Hole Center Along Width: 0.378 inches Second Leg Distance From Edge To Hole Center Along Length: 0.380 inches First Leg Thickness: 0.180 inches Second Leg Thickness: 0.180 inches First Leg Width: 2.750 inches First Leg Distance Between Hole Centers Along Width: 1.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.380 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square **Second Leg Hole Arrangement Style:** 

Four holes

Second Leg Relationship To First Leg:

Not identical

## NSN 5340-01-296-2086

Angle Bracket - Page 2 of 2

First Leg Angle:



90.0 degrees
Special Features:
0.646 in. Min and 0.666 in. Maximum hole dia; 0.750 in. From edge to hole center along w and 1.000 in. From edge to hole center along Ig
of seconded leg; 0.139 in. Min and 0.144 in. Maximum hole diameter two places; 0.532 in. From edge along the lg to hole center and 0.750
from edge to hole center along the w, second hole is 0.750 in. To hole center along the w and 1.469 in. To hole center along the lg; color
yellow
Material:
Steel
Material Specification:
Astm a36 assn standard single material response
Surface Treatment:
Chromate zinc
Surface Treatment Specification:
Tt-p-1757 federal specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0