

View Online at <https://aerobasegroup.com/nsn/5340-01-296-2086>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.000 inches

**Second Leg Length:**

2.500 inches

**Second Leg Width:**

2.750 inches

**First Leg Hole Diameter:**

Between 0.217 inches and 0.222 inches

**Second Leg Hole Diameter:**

Between 0.180 inches and 0.185 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.312 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.378 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.380 inches

**First Leg Thickness:**

0.180 inches

**Second Leg Thickness:**

0.180 inches

**First Leg Width:**

2.750 inches

**First Leg Distance Between Hole Centers Along Width:**

1.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.380 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

0.646 in. Min and 0.666 in. Maximum hole dia; 0.750 in. From edge to hole center along w and 1.000 in. From edge to hole center along lg of seconded leg; 0.139 in. Min and 0.144 in. Maximum hole diameter two places; 0.532 in. From edge along the lg to hole center and 0.750 from edge to hole center along the w, second hole is 0.750 in. To hole center along the w and 1.469 in. To hole center along the lg; color yellow

**Material:**

Steel

**Material Specification:**

Astm a36 assn standard single material response

**Surface Treatment:**

Chromate zinc

**Surface Treatment Specification:**

Tt-p-1757 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0