

View Online at <https://aerobasegroup.com/nsn/5340-01-296-7844>

Mounting Hole Type:

Plain

First Leg Length:

1.500 inches

Second Leg Length:

1.500 inches

Second Leg Width:

3.000 inches

Second Leg End Width:

2.800 inches

First Leg Slot Length:

0.750 inches

First Leg Slot Width:

0.280 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.120 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

Second Leg Slot Length:

0.750 inches

Second Leg Slot Width:

0.280 inches

First Leg Thickness:

0.062 inches

Second Leg Thickness:

0.062 inches

Center Section Height:

5.130 inches

Center Section Width:

1.690 inches

Center Section Thickness:

0.062 inches

First Leg Width:

1.690 inches

First Leg End Width:

1.490 inches

First Leg Distance From Edge To Hole Center Along Width:

0.630 inches

First Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

Opposite p/n 5267850-002

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 3, cl 1 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.