## NSN 5340-01-296-8783

Access Cover - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-296-8783

| Cross Sectional Shape:  |
|---|
| Square or rectangular recess  |
| Hole Diameter:  |
| 0.404 inches  |
| Width:  |
| 12.000 inches   |
| Edge Shape:   |
| Rectangle, no holes   |
| Length:   |
| 6.250 inches  |
| Corner Radius:  |
| Between 0.935 inches and 0.939 inches   |
| First Recess Inside Height:   |
| 4.300 inches  |
| Body Thickness:   |
| 0.400 inches  |
| Securing Device Type:   |
| Special   |
| Mounting Opening Shape Style:   |
| Unthreaded hole   |
| Inside Angle:   |
| 3.0 degrees   |
| Special Features:   |
| Central mtg hole counterbored 1.250 in. Diameter by 0.270 in. Dp w/bottom finish 63.0 microinches; eight reinforcing ribs radiating from    |
| center; side walls 0.130 in. Thk; internal peripheral aperture 32.0 microinch finish extending 0.620 in. From open end and incl a periphera |
| bevel 20.0 degrees by 0.180 in.; color black o/a; used w/valve package no. 2  |
| Material:   |
| Aluminum alloy 6061   |
| Material Specification:   |
| Qq-a-250/11-t6 federal specification single material response   |
| Surface Treatment:  |
| Anodize   |
| Surface Treatment Specification:  |
| Mil-a-8625, type 3, cl 2 military specification single treatment response   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A531c0  |

Mil-a-8625 spec.

Mil-std (military Standard):