NSN 5340-01-297-1518

Mounting Bracket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-297-1518

| | _ | | | |
|------|----------|------|--------|------|
| End | Λn | nlic | · atic | ۱n: |
| LIIU | Δ | DIIL | ,auc | ,,,, |

Light tables

Special Features:

Consists of 1 center idler bracket, p/n c30302-1, 1 center reel bracket, p/n b12084-1, 3 no. 8 round head drive screws, p/n 200287-6, 1 1/4-20 tap-lok insert, 2 0.312 in. Outside diameter by 0.060 in. Thick flat washers, p/n 201141, 2 - mod. Bronze bearings, p/n b32308-1, 1 - 1/8 in. Diameter tubular rivet, 1 - 1-3/8 in. Diameter knurled knob, p/n 401023, 1 - 1/4-20 spring plunger, p/n 401518, 1 3/16 in. Diameter ball, p/n 401639, 2 - 0.312 in. Outside diameter by 0.037 in. Thick flat washers, p/n 201140, 2 bearing spacers, p/n b32307-1 and permanent thdlkr adhesive, p/n 100196 as reuired

| - | | | | | | |
|----|----|-------|---|----|----|--|
| ٠. | he | . 1 + | | 18 | ο. | |
| J | | | _ | | ┖. | |

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0